

TEE HANDLE REMOTE CONTROL UNITS

Push-pull control for the operation of in-line, quarter turn ball valves or built-in eductors. Handle configuration allows identification/location label to be inserted.

PRODUCT INFORMATION	MODELS	
	RC-1	RC-7
Handle	Locking	Non-locking
Installation Diameter	1.9" (Pump panel)	1" (Pump panel)
Furnished with	2 ball joint swivel connectors	
Travel	11"	7.3", 9.8" or 11.3" <i>(specify)</i>
Material	Chrome-plated cast brass handle with anodized aluminum extrusion rod	
Weight	4 lbs.	1.5 lbs.



RC-1



REMOTE VALVE CONTROLS



RC-10 – SLOW CLOSING VALVE CONTROL


- Remote actuation of any ball valve
- Linear output screw-type actuator compliant with NFPA 1901 (as it pertains to slow-closing valves)
- Actuator and push-rod constructed of extruded aluminum alloys
- Precision needle thrust bearing and hardened thrust washers
- 5" cast alloy hand-wheel with collet-type connection allows for easy compact thru-panel installation (either new or retro-fit)
- Furnished with threaded ball swivel joint at end of drive rod
- Installation diameter: 1.03" (pump panel)
- Length: 16.4" (retracted) and 21.4" (extended)
- Weight: 3.2 lbs.
- Valve Status Indicator (optional)



VALVE STATUS INDICATOR

- Requires minimal pump panel space
- Tri-color indicators: red (closed), yellow (gated) and green (open)
- Feature 100,000 hour ultra bright LEDs mounted within an optical filter to maximize visibility in bright sunlight
- NEMA 4 rated
- Chrome bezel included

RC Accessories



775-5 – HANDLE

- For remote control screw type gate valve or gear driven valve
- Bored for .375" rod
- Material: Cast brass with chrome-plated finish
- Diameter: 4"
- Weight: 1.0 lbs.



775-11 – ROD GUIDE

- For centering and guiding remote control rod
- Nylon sleeve for 0.5" rod
- Material: Cast brass with chrome-plated finish
- Diameter: 1.5"
- Weight: 0.2 lbs.



775-15 – TEE HANDLE

- For use with push-pull rods to remotely operate in-line, quarter turn ball valves or built-in eductors
- Bored for 0.5" rod
- Can be threaded to .500" — 13 or .500" — 20 (specify)
- Handle configuration allows identification/location label to be inserted
- Material: Cast brass with chrome-plated finish
- Height: 1.1"
- Weight: 0.5 lbs.

UNIBODY HAND-WHEEL

POSITION INDICATING

PRODUCT INFORMATION	MODELS	
	GWP-4	GWP-6
Hand-wheel diameter	4"	6"
Material	Stainless Steel	
Finish	Stainless Steel	
Type	Position Indicating	
Installation diameter	1.312"	
Weight	3.6 lbs.	4.1 lbs.



GWP-4



GWP-6

PANEL MOUNT



PRODUCT INFORMATION	MODELS	
	GWR-5	GWR-6.5
Hand-wheel diameter	5"	6.5"
Material	Brass	
Finish (<i>specify</i>)	Chrome	
Type	Panel Mount	
Installation diameter	1.125"	
Furnished with	Panel bushing and two universal swivel joints with protective rubber boots	
Weight	6.0 lbs.	7.0 lbs.

DIRECT MOUNT

PRODUCT INFORMATION	MODELS	
	GWD-5	GWD-6.5
Hand-wheel diameter	5"	6.5"
Material	Brass	
Finish (<i>specify</i>)	Chrome	
Type	Direct Mount	
Installation diameter	-	
Furnished with	-	
Weight	6.0 lbs.	7.0 lbs.