

HANDLINE NOZZLES



CHIEF™

Chief™

Fixed flow Chief™ nozzles efficiently deliver a constant gallonage from straight stream to full fog. The simple rugged design makes the Chief™ easy to use, train with and reliable in tough situations. Superior hydraulics due to a fully machined waterway result in excellent stream quality and reach. The Chief™ is also available in true low pressure versions with specifically engineered, calibrated and labeled stems down to 50 psi. With more than 300 available variations the Chief™ is easily customized to meet your specific needs.

HANDLINE NOZZLES

1-9



British Standard Parallel Pipe (BSPP) and British Instantaneous (BS336) base options available.

| BASE SIZE | PSI (BAR) | AVAILABLE STANDARD FLOW RATE GPM (LPM) | | | | | | | | | | | | | | BASE TYPE | | | SHUT-OFF | HANDLE | TEETH | | | MODEL | | | | | | |
|-----------|------------|---|----------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|------------|-------|----------|--------|--------|-------------|-------|-------|------|-----|-----------|------------------|-----------------|-----------|
| | | 15 (57) | 30 (114) | 45 (170) | 60 (227) | 75 (284) | 95 (360) | 125 (473) | 150 (568) | 175 (662) | 185 (700) | 200 (757) | 250 (946) | 275 (1041) | 300 (1136) | 325 (1230) | 350 (1325) | Rigid | | | Swivel | Free Swivel | Twist | | Ball | Tab | Horseshoe | Spinning Plastic | Molded Urethane | Cut Metal |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1" | 100 (6.89) | • | • | • | • | | | | | | | | | | | | | | s | | | | | | s | | | 4000-04 | Chief Tips | |
| | 50 (3.45) | 75 (5.17) | | | | | | | × | × | × | | | | | | | | o | s | | | | | | s | o | 4000-14 | | |
| | | 100 (6.89) | | | | • | | | × | × | × | | | | | | | | | | | | | | | | | | | |
| | | 50 (3.45) | | | | | | | | | | 160 | × | | | | | | | s | | | | | | | s | | | 4000-14HR |
| | 1.5" | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 50 (3.45) | | | | • | | | | | | | | | | | | | | | | | | | | s | o | | | 4000-19 |
| | | 75 (5.17) | | | | • | | | | | | | | | | | | | | | | | | | | s | o | | | 4000-22 |
| | | 100 (6.89) | | | | • | | | | | | | | | | | | | | | | | | | | s | o | | | 4000-22 |
| | | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.5" | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | 4000-24 | |
| | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | 4000-24 | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | 4000-22 | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | 4000-24 | |



| BASE SIZE | PSI (BAR) | AVAILABLE STANDARD FLOW RATE GPM (LPM) | | | | | | | | | | | | | | BASE TYPE | | | SHUT-OFF | HANDLE | TEETH | | | MODEL | | | | | | | |
|-----------|------------|---|----------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|------------|-------|----------|--------|--------|-------------|-------|-------|------|-----|-----------|------------------|-----------------|-----------|--|
| | | 15 (57) | 30 (114) | 45 (170) | 60 (227) | 75 (284) | 95 (360) | 125 (473) | 150 (568) | 175 (662) | 185 (700) | 200 (757) | 250 (946) | 275 (1041) | 300 (1136) | 325 (1230) | 350 (1325) | Rigid | | | Swivel | Free Swivel | Twist | | Ball | Tab | Horseshoe | Spinning Plastic | Molded Urethane | Cut Metal | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1" | 100 (6.89) | • | • | • | • | | | | | | | | | | | | | | s | | | | • | s | o | s | | 4000-02 | Chief Nozzles | | |
| | 50 (3.45) | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 100 (6.89) | | | | • | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1.5" | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 50 (3.45) | | | | • | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 75 (5.17) | | | | • | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 100 (6.89) | | | | • | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.5" | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



Key: s = Standard o = Option
 ✕ = Flow rates available on the Chief XD
 • = Flow rates not available on the Chief XD

HANDLELINE NOZZLES



CHIEF™

HANDLELINE NOZZLES

1-11

| BASE SIZE | PSI (BAR) | AVAILABLE STANDARD FLOW RATE GPM (LPM) | | | | | | | | | | | | | | BASE TYPE | | | SHUT-OFF | | HANDLE | | | TEETH | | | MODEL | | | |
|-----------|------------|---|----------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|--------------|------------|-------|----------|-------------|--------|-------|-----|-----------|------------------|-----------------|-------|------------|--|---------|
| | | 15 (57) | 30 (114) | 45 (170) | 60 (227) | 75 (284) | 95 (360) | 125 (473) | 150 (568) | 175 (662) | 185 (700) | 200 (757) | 250 (946) | 275 (1041) | 300 (1136) | 325 (1230) | 350 (1325) | Rigid | Swivel | Free Swivel | Long | Short | Tab | Horseshoe | Spinning Plastic | Molded Urethane | | Curt Metal | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1" | 100 (6.89) | • | • | • | • | | | | | | | | | | | | | | | s | | | • | s | o | s | | | | 4000-03 |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | 4000-13 |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | s | | | • | o | s | s | o | | | 4000-17 |
| 1.5" | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | 4000-23 |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | s | | | • | o | s | s | o | | | 4000-28 |
| | 100 (6.89) | | | | | | | | | | | | | | | | | | o | s | | | • | o | s | s | o | | | |
| 2.5" | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 100 (6.89) | | | | | | | | | | | | | | | | | s | | o | | | • | o | s | s | o | | | |



| | | | | | | | | | | | | | |
|----|---|--|--|---|---|---|--|--|--|--|--|--|----------------|
| 1" | 15-20 GPM @ 1100-1500 PSI (57-76 LPM @ 76-103 BAR) Flow & Pressure are factory set and must be specified when ordering. | s - SS HEX NPT o - Free Swivel o - Quick Connect | | • | o | s | | | | | | | 4000-03 UHP |
|----|---|--|--|---|---|---|--|--|--|--|--|--|----------------|



Key: s = Standard o = Option
 X = Flow rates available on the Chief XD
 • = Flow rates not available on the Chief XD

OPTIONS

| HANDLES | | MOLDED URETHANE TEETH | | | | | | |
|--|---------------|---|-----|--------|--------|------|-------|------|
| TAB | HORSESHOE | | | | | | | |
| THREADS | | COLORS | | | | | | |
| All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads, including British instantaneous. | | black | red | orange | yellow | Glow | green | blue |
| | | Color options available for pistol grip, bumper, and handle. Glow available for bumper only. Retrofit kit available for Glow bumper. White bumper not available. | | | | | | |
| | | Chief™ nozzle comes standard with an orange bumper, chrome handle, and natural Elk-O-Lite® pistol grip. | | | | | | |

| ADDITIONAL INFORMATION | |
|-----------------------------|--------|
| PART NAME | PAGE # |
| Thread Information | T-13 |
| Nozzle Flow Data | T-2 |
| Hose and Nozzle Accessories | 2-1 |
| Foam Expansion Tubes | 2-2 |