













HANDLINE NOZZLES





















SELECTOR GUIDE










HANDLINE NOZZLES

1-1

	AVAILABLE BASE	PRODUCT	DESCRIPTION	MATERIAL		"QUICK-KEY"					
				Brass	Elk-O-Lite®						
FIXED CHIEF XD™ & XD SHUTOFFS	<table border="1"> <tr> <td>1.0</td> <td>1.5</td> <td>2.5</td> </tr> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </table> Available GPM (LPM) 95-300 (360-1136)	1.0	1.5	2.5	•	•	•	 <i>Page 1-4</i> <ul style="list-style-type: none"> Dual drive shutoff with full round metal ball Forged Aluminum shutoff body and bale handle Spinning stainless steel Fixed flow 	Brass	Elk-O-Lite®	
1.0	1.5	2.5									
•	•	•									
FIXED CHIEF™	<table border="1"> <tr> <td>1.0</td> <td>1.5</td> <td>2.5</td> </tr> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </table> Available GPM (LPM) 15-350 (57-1325)	1.0	1.5	2.5	•	•	•	 <i>Page 1-9</i> <ul style="list-style-type: none"> Wide selection of flow and pressure Ideal for low pressure use Fixed flow 	Brass	Elk-O-Lite®	
1.0	1.5	2.5									
•	•	•									
AUTOMATIC SELECT-O-MATIC®	<table border="1"> <tr> <td>1.0</td> <td>1.5</td> <td>2.5</td> </tr> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </table> Available GPM (LPM) 10-325 (38-1230)	1.0	1.5	2.5	•	•	•	 <i>Page 1-12</i> <ul style="list-style-type: none"> Maintains effective stream reach throughout flow range Ideal for AFFF application Wide flow range / automatic flow 	Brass	Elk-O-Lite®	
1.0	1.5	2.5									
•	•	•									
SELECTABLE PHANTOM®	<table border="1"> <tr> <td>1.0</td> <td>1.5</td> <td>2.5</td> </tr> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </table> Available GPM (LPM) 15-200 (57-757)	1.0	1.5	2.5	•	•	•	 <i>Page 1-15</i> <ul style="list-style-type: none"> Firefighter chooses flow and stream Rugged and easy to use Wide flow range/constant flow 	Brass	Elk-O-Lite®	
1.0	1.5	2.5									
•	•	•									
SELECTABLE SELECT-O-FLOW®	<table border="1"> <tr> <td>1.0</td> <td>1.5</td> <td>2.5</td> </tr> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </table> Available GPM (LPM) 40-250 (151-946)	1.0	1.5	2.5	•	•	•	 <i>Page 1-17</i> <ul style="list-style-type: none"> Firefighter chooses flow and stream High flow range/constant flow Rugged all brass versions 	Brass	Elk-O-Lite®	
1.0	1.5	2.5									
•	•	•									
VARIABLE MYSTERY®	<table border="1"> <tr> <td>1.0</td> <td>1.5</td> <td>2.5</td> </tr> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </table> Available GPM (LPM) 60-250 (227-946)	1.0	1.5	2.5	•	•	•	 <i>Page 1-19</i> <ul style="list-style-type: none"> Original fog nozzle Variable flow 	Brass	Elk-O-Lite®	
1.0	1.5	2.5									
•	•	•									

		AVAILABLE BASE			PRODUCT		DESCRIPTION		MATERIAL		"QUICK-KEY"	
FIXED	SELECT-O-STREAM®	1.0	1.5	2.5		<i>Page 1-21</i>	<ul style="list-style-type: none"> Convenient detents for stream selection Rugged all brass construction with chrome finish Fixed Flow 	Brass	Elk-O-Lite®	 		
		Available GPM (LPM) 60-250 (227-946)						•				
FIXED/VARIABLE	INDUSTRIAL FOG & ELECTRICAL FOG	1.0	1.5	2.5		<i>Page 1-23</i>	<ul style="list-style-type: none"> Durable and simple to use Designed for corrosive conditions For use on Class "C" fires Narrow to wide fog only 	Brass	Elk-O-Lite®	  		
		Available GPM (LPM) 12-250 (45-946)						•				
FIXED	MARINE	1.0	1.5	2.5		<i>Page 1-25</i>	<ul style="list-style-type: none"> 85-5-5-5 Brass construction Designed for corrosive conditions Accepted US Navy Specifications 	Brass	Elk-O-Lite®	   		
		Available GPM (LPM) 95-250 (360-946)						•				
	BALL SHUT-OFFS, & PLAYPIPES	1.0	1.5	2.5	 	<i>Page 1-6</i> <i>Page 1-27</i>	<ul style="list-style-type: none"> Wide range of flows Smooth bore optional Design your own break-apart Playpipes for easy handling 	Brass	Elk-O-Lite®			
		Available GPM (LPM) 118-209 (447-791)						•			•	
	SPECIAL USE	1.0	1.5	2.5		<i>Page 1-35</i>	<ul style="list-style-type: none"> Forestry Wat-R-Wall Cellar Bresnan 	Brass	Elk-O-Lite®	 		
		Available GPM (LPM)						•			•	

KEY:

								
Low Pressure Available	Ball Shut-off Available	Twist Shut-off Available	Rebuild/Retro Available	Electrical	Foam Compatible	U.S. Coast Guard/Navy Approved	Underwriters Laboratories	Factory Mutual