

Giant Python®

- 2500 gpm flow capacity — 3.5" waterway with seamless tube construction
- Double hand-wheel control for ease of operation and positive lock in any position
- All construction features designed to minimize maintenance needs
 - #304 stainless steel construction
 - Cast stainless swivel joints
 - Stainless steel balls in all swivel joints
 - Hand-wheel driven worm gears
- Liquid-filled pressure gauge



Hand-wheel rotates with monitor for continuous 360° horizontal travel

Red urethane finish

3.5" flow-efficient waterway

**200
PSI**

**2500
GPM**



Giant Python
Mo. 299-20
(Nozzle sold separately)









GIANT PYTHON®

Giant Python® Selector Guide

| INLET SIZES / TYPES | | | | | | | | OUTLET SIZE | CERTIFICATIONS | | MODEL |
|---------------------|----|------------------|----|----|------------------|----|----|-------------|----------------|-------------|---------------------|
| NPT | | 150# ANSI Flange | | | 300# ANSI Flange | | | 3.5" | CE | FM Approved | |
| 3" | 4" | 3" | 4" | 6" | 3" | 4" | 6" | | | | |
| o | o | o | s | o | o | o | o | • | • | • | 299-20 |
| | | | 1 | | | | | | | | <i>Illustration</i> |

KEY s = standard o = option

Recommended Products

| CJK – MYSTERY® | SM-2000B – X-STREAM® | SM-2000HF – SELF-EDUCTING | 181-3 – DELUGE TIP | 284B – STREAM SHAPER | 84 – BUTTERFLY WAFER VALVE |
|---|---|---|---|--|---|
|  |  |  |  |  |  |
| <i>Page 6-14</i> | <i>Page 6-7</i> | <i>Page 6-16</i> | <i>Page 1-26</i> | <i>Page 1-27</i> | <i>Page 5-51</i> |

5-46

Components & Options Chart

| COMPONENTS & OPTIONS | ILLUSTRATION | MODEL |
|-----------------------|--|----------|
| Companion Flange Kits | 3" 150# ANSI steel flange with bolts and gaskets | 81315001 |
| | 4" 150# ANSI steel flange with bolts and gaskets | 81317001 |

| SPECIFICATIONS | | | | |
|----------------------------|---|------------------|------------------|---------|
| Max. GPM (LPM) | 2500 (9463) | | | |
| Inlets | Sizes | | Types | |
| | 6" | 150# ANSI Flange | 300# ANSI Flange | |
| | 4" | 150# ANSI Flange | 300# ANSI Flange | NPT (F) |
| | 3" | 150# ANSI Flange | 300# ANSI Flange | NPT (F) |
| Outlet Size | 3.5" NHT | | | |
| Controls | Dual hand-wheel | | | |
| Material/Finish | Stainless steel with red urethane enamel and brass trim | | | |
| Friction Loss | 18 psi at 2500 gpm | | | |
| | 6 psi at 1250 gpm | | | |
| Travel | V -60° to +90° (150°) | | | |
| | H 360° (continuous) | | | |
| Weight | 126.00 Lbs. | | | |
| Ratings and Certifications | FM Approved, CE | | | |

ADDITIONAL INFORMATION

- All flanges specified with the monitor are flat faced. Raised face flanges are available with some inlet sizes. Please inquire with our sales staff.
- Technical Data on monitor performance may be found on page T-11.