

Adapters

In the over 100 years Elkhart has been a fire service manufacturer, we have created a wide assortment of standardized adapters to meet the varied needs of the fire industry. This extensive selection includes thread adapters to suit any need — whether for a male to female; a suction adapter with built-in strainer, NHT, NPT or custom order; or even for a universal adapter — you can find the perfect fit here.

- A selection of rocker lug and pin lug options
- Aluminum, Brass, and Chrome finishes available

Adapter
Mo. M-327



High Rise Elbow
Mo. 105A



Several material options — lightweight Elk-O-Lite® or durable cast brass (including some with chrome-plated finish)

ADAPTERS, CAPS & PLUGS



HOSE TO HOSE ADAPTERS

ADAPTERS, CAPS & PLUGS

11-3

What kind of adapter do you need?																							
Step 1: Select Material	Step 2: Choose Connection Type (Inlet to Outlet)	Step 3: Determine Gender (Inlet to Outlet)	Step 4: Select from available options														Step 5: Pick Model Model	Figure					
			Inlet	Size (Inches)										Construction		Type							
				1	1.5	2	2.5	3	3.5	4	4.5	5	6	Solid	Swivel	Hex			Internal Lug	Long Handle	Rocker		
Brass	Hose Thread to Hose Thread	NHT (M) to NHT (F)	1	•											•				s	A-327	9		
			1.5		•										•					s	D-327	8	
			1.5	•		•									•					s	A-327*	9	
			1.5			•									•					s	S-327	11	
			2												•						s	A-327	9
			2.5	•		•	•								•					s	S-327	11	
			2.5			•	•								•			s		s	105	3	
			2.5			•	•								•						s	A-327	9
			3			•	•								•						s	S-327	11
			3			•	•								•			s			s	105	3
		3			•	•								•						s	A-327	9	
		3			•	•								•			s			s	S-327	11	
		3			•	•								•						s	105	3	
		3.5							•							•				s			
		1.5	•	•	•											•					s	A-327	9
		2.5	•	•												•					s	D-327	8
		2.5	•	•	•	•										•					s	A-327*	9
		2.5	•	•	•	•										•			s	s	S-327	11	
		2.5	•	•	•	•										•				s	105	3	
		3		•	•	•										•				s	A-327	9	
3		•	•	•										•			s	s	S-327	11			
3		•	•	•										•				s	105	3			
3.5		•	•	•										•				s					
NHT (M) to NHT (M)	1.5	•												•					s	M-327	6		
NHT (F) to NHT (F)	1.5	•												•					s	F-327	1		
	2.5		•											•					s	F-327	1		
	3				•									•					s	S-319	3		
	4.5									•	•	•					s						
Aluminum	Hose Thread to Hose Thread	NHT (M) to NHT (F)	1.5			•									•					s	D-327A	7	
			1.5	•		•									•					s	A-327A	10	
		2.5			•										•					s	A-327A	10	
		NHT (F) to NHT (M)	1.5	•												•				s	D-327A	7	
		2.5	•		•										•					s	M-327A	4	
		2.5	•		•											•				s	M-327ABI	5	
		NHT (M) to NHT (M)	1.5	•												•				s	F-327A	2	
		2.5			•											•				s			
		NHT (F) to NHT (F)	1.5	•												•					s		
		2.5			•											•				s			

Key s = standard o = option

* A327 has optional pin lug and chrome finish in the 2.5F by 1.5M/1.5M by 2.5F size.

OPTIONS THREADS

NHT can also be called NST. See T-13 for optional threads.

MEASUREMENTS

Length measurements shown on page T-15.

UNIVERSAL ADAPTER



435

- Cast brass construction with chrome-plated finish
- Adapts any 2.5" hose thread to 2.5" NHT
- Positive ratchet lock with thumb release
- Weight: 6.42 lbs.

	FEMALE/FEMALE	MALE/MALE	MIXED
Figure 1	 <p>F-327</p> <ul style="list-style-type: none"> • Double swivel female • Cast brass finish (chrome optional) <p><i>Fig. 1</i></p>	 <p>M-327A</p> <ul style="list-style-type: none"> • Double male <p><i>Fig. 4</i></p>	 <p>D-327A</p> <ul style="list-style-type: none"> • Direct connect adapter <p><i>Fig. 7</i></p>
Figure 2	 <p>F-327A</p> <ul style="list-style-type: none"> • Double swivel female <p><i>Fig. 2</i></p>	 <p>M-327ABI</p> <ul style="list-style-type: none"> • Double male British Instantaneous <p><i>Fig. 5</i></p>	 <p>D-327</p> <ul style="list-style-type: none"> • Direct connect adapter • Chrome finish (cast brass optional) <p><i>Fig. 8</i></p>
Figure 3	 <p>105</p> <ul style="list-style-type: none"> • 45° discharge elbow • Female rocker lug • Chrome finish <p><i>Fig. 3</i></p>	 <p>M-327</p> <ul style="list-style-type: none"> • Double male • Cast brass finish (chrome optional) <p><i>Fig. 6</i></p>	 <p>A-327</p> <ul style="list-style-type: none"> • Female rocker lug <p><i>Fig. 9</i></p>
<p>ADDITIONAL INFORMATION</p> <p><i>When ordering, specify: model number; inlet size, gender, and thread; outlet size, gender, and thread; as well as any optional type or finish information.</i></p>			
<p>105A High Rise Elbow</p> <ul style="list-style-type: none"> • 45° drain elbow • 2.5" Female free swivel • 2.5" Male discharge • Integrated Model 114 drain valve • 250 GPM flow • 200 PSI operating pressure • 1 lb. 3 oz. 			
Figure 10			 <p>A-327A</p> <ul style="list-style-type: none"> • Female rocker lug <p><i>Fig. 10</i></p>
Figure 11			 <p>S-327</p> <ul style="list-style-type: none"> • Internal lug body • External female rocker lug • Cast brass finish (chrome optional) <p><i>Fig. 11</i></p>